

V-6 Submersible Pumps (142mm O.D.) Mixed Flow

C.I. Bowl / S.S. Impeller (Q-Type)

Model V-6-125	DISCHARGE IN L.P.M.				00	250	350	450	550	650	780
	Sr. No.	H.P.	STG	Del. in Inch	Total Head in Mtrs.						
	1	5.00	4	2.50"	42	37	34	31	29	22	14
	2	6.00	5	2.50"	53	47	43	38	35	27	18
	3	7.50	6	2.50"	64	57	54	47	43	33	20
	4	10.00	8	2.50"	86	79	71	63	57	44	26
	5	12.50	10	2.50"	107	98	89	80	70	55	33
	6	15.00	12	2.50"	131	119	110	100	86	68	40

Model V-6-150	DISCHARGE IN L.P.M.				00	300	400	500	600	700	820
	Sr. No.	H.P.	STG	Del. in Inch	Total Head in Mtrs.						
	7	5.00	3	2.50"	32	29	27	24	22	19	17
	8	6.00	4	2.50"	41	37	34	32	29	25	21
	9	7.50	5	2.50"	51	47	43	40	36	31	26
	10	10.00	7	2.50"	72	65	61	57	51	43	35
	11	12.50	8	2.50"	83	74	68	63	58	48	39
	12	15.00	10	2.50"	105	93	86	79	73	61	48

Model V-6-200	DISCHARGE IN L.P.M.				00	500	600	700	800	900	1100
	Sr. No.	H.P.	STG	Del. in Inch	Total Head in Mtrs.						
	13	6.00	3	3.00"	35	29	27	25	23	20	13
	14	7.50	4	3.00"	47	38	36	34	31	27	18
	15	10.00	5	3.00"	59	48	45	43	39	34	22
	16	12.50	6	3.00"	71	57	54	51	47	41	26
	17	15.00	7	3.00"	83	67	63	60	55	48	30
	18	15.00	8	3.00"	94	77	72	69	62	54	35

Model V-6-250	DISCHARGE IN L.P.M.				00	600	700	800	900	1000	1200
	Sr. No.	H.P.	STG	Del. in Inch	Total Head in Mtrs.						
	19	7.50	3	3.00"	42	33	30	27	25	22	18
	20	10.00	4	3.00"	57	42	39	36	33	31	23
	21	12.50	5	3.00"	67	51	48	45	41	37	27
	22	15.00	6	3.00"	80	60	56	53	49	44	33