

V-6 Submersible Pumps (142mm O.D.) Radial Flow S.S. Bowl / S.S. Impeller

Model V-6-125	DISCHARGE IN L.P.M.						200	280	310	340	380	430	475	550
	Sr. No.	H.P.	STG	Del. in Inch	ISI Model	Star Rating	Total Head in Mtrs.							
	26	5.00	4	2.50"	ISI	5-Star	60	56	52	48	44	40	32	20
	27	6.00	5	2.50"	ISI	5-Star	75	70	65	60	55	50	40	25
	28	7.50	6	2.50"	ISI	5-Star	90	84	78	72	66	60	48	30
	29	10.00	8	2.50"	ISI	5-Star	120	112	104	96	88	80	64	40
	30	12.50	10	2.50"	ISI	5-Star	150	140	130	120	110	100	80	50
	31	15.00	12	2.50"	ISI	5-Star	180	168	156	144	132	120	96	60
	32	17.50	14	2.50"	-	-	210	196	182	168	154	140	112	70
	33	20.00	16	2.50"	-	-	240	224	208	192	176	160	128	80

Model V-6-150	DISCHARGE IN L.P.M.						240	320	370	410	440	470	510	580
	Sr. No.	H.P.	STG	Del. in Inch	ISI Model	Star Rating	Total Head in Mtrs.							
	34	3.00	2	2.50"	-	-	30	28	26	24	22	20	16	10
	35	5.00	3	2.50"	ISI	5-Star	45	42	39	36	33	30	24	15
	36	6.00	4	2.50"	ISI	5-Star	60	56	52	48	44	40	32	20
	37	7.50	5	2.50"	ISI	5-Star	75	70	65	60	55	50	40	25
	38	10.00	7	2.50"	ISI	5-Star	105	98	91	84	77	70	56	35
	39	12.50	8	2.50"	ISI	5-Star	120	112	104	96	88	80	64	40
	40	15.00	10	2.50"	ISI	5-Star	150	140	130	120	110	100	80	50
	41	17.50	12	2.50"	-	-	180	168	156	144	132	120	96	60
	42	20.00	13	2.50"	-	-	195	180	169	156	143	130	104	65

Model V-6-200	DISCHARGE IN L.P.M.						280	370	430	500	540	580	650	750
	Sr. No.	H.P.	STG	Del. in Inch	ISI Model	Star Rating	Total Head in Mtrs.							
	43	6.00	3	2.50"	-	-	45	42	39	36	33	30	24	15
	44	7.50	4	2.50"	-	-	60	56	52	48	44	40	32	20
	45	10.00	5	2.50"	-	-	75	70	65	60	55	50	40	25
	46	12.50	6	2.50"	-	-	90	84	78	72	66	60	48	30
	47	15.00	8	2.50"	-	-	120	112	104	96	88	80	64	40
	48	17.50	9	2.50"	-	-	135	126	117	108	99	90	72	45
	49	20.00	10	2.50"	-	-	150	140	130	120	110	100	80	50